

# LVQMRC Safety Inspection Sheet (Rev 120618)

Tech \_\_\_\_\_ Owner \_\_\_\_\_ Class \_\_\_\_\_ Car # \_\_\_\_\_ Pass Date \_\_\_\_\_

Use a check mark for PASS and an X for FAIL

|                                                                                                                                                                                                                                  | 1 <sup>st</sup> | 2 <sup>nd</sup> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|
| 1. Belly pan must go from firewall to in front of the driver's feet. ....                                                                                                                                                        | ___             | ___             |
| 1a. Minimum thickness of .025 for steel (check with magnet), .048 for aluminum.....                                                                                                                                              | ___             | ___             |
| 2. Must have 2.5" hole in the tail or easily removable winged Dzus Buttons or clips .....                                                                                                                                        | ___             | ___             |
| 3. Must have complete firewall, 0.48 for aluminum, 0.25 for steel.....                                                                                                                                                           | ___             | ___             |
| 4. High Back Kirky style seat is highly recommended, bottom of seat no more than 8" from ground. ....                                                                                                                            | ___             | ___             |
| 4a. Must be attached with 5/16" bolts, 2 on bottom, 2 on back. ....                                                                                                                                                              | ___             | ___             |
| 5. Steering wheel pad and check quick release. ....                                                                                                                                                                              | ___             | ___             |
| 6. Static break check.....                                                                                                                                                                                                       | ___             | ___             |
| 7. Front and rear bumpers fastened with bolts & nuts required. Of STURDY construction with no sharp edges or protrusions. ....                                                                                                   | ___             | ___             |
| 8. Nerf bars fastened with nuts & bolts are required in front of rear tires. They must extend beyond the center of the rear tires but not past the outside of the rear tires and of STURDY construction. ....                    | ___             | ___             |
| 9. Must have an ignition switch on the left side of the cockpit. Also, a switch must be mounted on the top left of the roll cage and it must have a 4" pigtail on it for red plate only. ON position must be up or forward ..... | ___             | ___             |
| 10. Five (5) point seat harness is required. ....                                                                                                                                                                                | ___             | ___             |
| 10a. Belts cannot be more than five (5) years old.....                                                                                                                                                                           | ___             | ___             |
| 11. Seat belt mounting must be approved by tech. ....                                                                                                                                                                            | ___             | ___             |
| 12. Helmets must be Snell 2010 or newer.....                                                                                                                                                                                     | ___             | ___             |
| 13. Neck collars, arm restraints and gloves are required. SFI Jacket and Jeans or a full suit must be worn .....                                                                                                                 | ___             | ___             |
| 14. Metal gas tank required. Two (2) fasteners are required to hold tank, tank must be cushioned, cap must be non-vented, and tank must have a ¼ turn shutoff valve.....                                                         | ___             | ___             |
| 15. Ballast (extra weight, not part of car) attached to metal thicker than .090 for aluminum or .058 for steel. Ballast must be fastened securely between frame rails, subject to tech approval. ....                            | ___             | ___             |
| 15a. Weight must be painted white.....                                                                                                                                                                                           | ___             | ___             |
| 16. Sufficient head support behind driver's head if not in a seat.....                                                                                                                                                           | ___             | ___             |