

LVQMRC Safety Inspection Sheet (Rev 120618)

Tech _____ Owner _____ Class _____ Car # _____ Pass Date _____

Use a check mark for PASS and an X for FAIL

	1 st	2 nd
1. Belly pan must go from firewall to in front of the driver's feet.	___	___
1a. Minimum thickness of .025 for steel (check with magnet), .048 for aluminum.....	___	___
2. Must have 2.5" hole in the tail or easily removable winged Dzus Buttons or clips	___	___
3. Must have complete firewall, 0.48 for aluminum, 0.25 for steel.....	___	___
4. High Back Kirky style seat is highly recommended, bottom of seat no more than 8" from ground.	___	___
4a. Must be attached with 5/16" bolts, 2 on bottom, 2 on back.	___	___
5. Steering wheel pad and check quick release.	___	___
6. Static break check.....	___	___
7. Front and rear bumpers fastened with bolts & nuts required. Of STURDY construction with no sharp edges or protrusions.	___	___
8. Nerf bars fastened with nuts & bolts are required in front of rear tires. They must extend beyond the center of the rear tires but not past the outside of the rear tires and of STURDY construction.	___	___
9. Must have an ignition switch on the left side of the cockpit. Also, a switch must be mounted on the top left of the roll cage and it must have a 4" pigtail on it for red plate only. ON position must be up or forward	___	___
10. Five (5) point seat harness is required.	___	___
10a. Belts cannot be more than five (5) years old.....	___	___
11. Seat belt mounting must be approved by tech.	___	___
12. Helmets must be Snell 2015 or newer.....	___	___
13. Neck collars, arm restraints and gloves are required. SFI Jacket and Jeans or a full suit must be worn	___	___
14. Metal gas tank required. Two (2) fasteners are required to hold tank, tank must be cushioned, cap must be non-vented, and tank must have a ¼ turn shutoff valve.....	___	___
15. Ballast (extra weight, not part of car) attached to metal thicker than .090 for aluminum or .058 for steel. Ballast must be fastened securely between frame rails, subject to tech approval.	___	___
15a. Weight must be painted white.....	___	___
16. Sufficient head support behind driver's head if not in a seat.....	___	___